# **Asymmetrical Horn TP Antenna**

## HORN ANTENNA WITH TWISTPORT<sup>™</sup> CONNECTOR


Asymmetrical Horn TP Antenna combines the best of both worlds - high gain of a traditional sector antenna and zero side lobes of a horn. Its radiation pattern is wide in azimuthal and narrow in elevation plane, greatly improving coverage planning options. Asymmetrical Horn TP Antenna exceeds the traditional patch sector antenna thanks to high stability of gain and radiation pattern in the whole band of operation. Outstanding noise rejection and precision of radiation pattern favors Asymmetrical Horn TP antenna for high-density AP clusters, in sprasely populated areas and dense co-location sites.


Asymmetrical Horn TP Antenna features our revolutionary TwistPort<sup>™</sup> connector - a patentpending twist-and-lock waveguide port. TwistPort<sup>™</sup> is virtually lossless and embodies a complete shift of paradigm in wireless network scalability and convenience of deployment. Asymmetrical Horn TP Antenna supports a wide range of third party mainstream radios with our TPA TwistPort<sup>™</sup> Adaptor.

#### **TECHNICAL DATA**


Antenna Connection	TwistPort™ - Quick Locking Waveguide Port					
Antenna Type	Horn					
Materials	UV Resistant ABS Plastic, Polycarbonate, HDPE, Aluminium, Stainless Steel					
Enviromental	IP55					
Pole Mounting Diameter	22-80 mm					
Temperature	-35°C to +55°C (-31°F to +131°F)					
Wind Survival	160 km/hour					
Mechanical Tilt	± 25°					
Weight	6.5 Kg / 14.3 lbs – single unit* 7.0 Kg / 15.4 lbs – single unit incl. package*					
Single Unit	Retail Box: 41.2 × 40.0 × 40.0 cm*					


#### PRODUCT DIMENSIONS






**ELEMENTS**<sup>®</sup>







RF elements® and TwistPort™ are trademarks of RF elements s.r.o., Humenne, Slovakia. All rights of respective trademark owners reserved. © RF elements 2019


## PERFORMANCE

Frequency Range	5180 - 6000 MHz
Gain	20.5 dBi
Azimuth Beam Width -3 dB	H 21°/V 21°
Elevation Beam Width -3 dB	H 15°/V 15°
Azimuth Beam Width -6 dB	H 30° / V 30°
Elevation Beam Width -6 dB	H 20° / V 20°
Front-to-Back Ratio	35 dB

#### **AZIMUTH PATTERN**



**ELEVATION PATTERN** 



\*Subject to chang

1/2 ASYMMETRICAL HORN ANTENNAS Rev FEB-2019



### **3D RADIATION DIAGRAM**

SCALE: 30dBi COMPATIBLE WITH: ADOBE ACROBAT READER DC. NOT SUPPORTED ON MOBILE. USE MOUSE TO ROTATE THE DIAGRAM. SCROLL IN/OUT TO ZOOM IN/OUT

dBi

									1	1												
20.5	19	17.5	16	14.5	13	11.5	10	8.5	7	5.5	5	4	2.5	1	-0.	5	-2	-3.5	-5	-6.5	-8	-9.5

FRONT	ВАСК	RIGHT	LEFT	UP	DOWN
2/2 ASYMMETRICAL HORN ANTENNAS Rev FE	EB-2019		RF elements <sup>®</sup> and Twist		ments s.r.o., Humenne, Slovakia tive trademark owners reserved
www.rfelements.com					© RF elements 2019