

# TwistPort™ Adaptor for ePMP-B-6

INTEGRATES EPMP CONNECTORIZED RADIOS  
INTO TWISTPORT™ ECO-SYSTEM

The TwistPort™ Adaptor TPA-ePMP-B-6 makes the ePMP™ 4600L and ePMP™ 4600C radio compatible with TwistPort™ Antennas that support 6 GHz band. TwistPort™ Adaptors are equipped with our original quick-locking waveguide port. Connecting and disconnecting the radios with the TwistPort™ Adaptor is very simple and requires no tools.



## TECHNICAL DATA

|                    |   |
|--------------------|---|
| Antenna Connection | TwistPort™ - Quick-Locking Waveguide Port   |
| Radio Connection   | 2x Slide-On RP-SMA  |
| Materials          | UV Resistant ABS plastic, Aluminium Alloy   |
| Flame Rating       | UL 94 HB  |
| Environmental      | IP65  |
| Temperature        | -40°C to +60°C (-40°F to +140°F)  |
| Wind Survival      | 160 km/h (100 mi/h)   |
| Weight             | 0.45 kg / 1.0 lbs – single unit<br>0.55 kg / 1.2 lbs – single unit incl. package<br>12.0 kg / 26.4 lbs – wholesale box (20 units)                 |
| Dimensions         | Single unit retail box:<br>157 x 171 x 128 mm (6.2 x 6.7 x 5.0 inch)<br>Wholesale box (20 units):<br>273 x 330 x 872 mm (10.7 x 13.0 x 34.3 inch) |

## PERFORMANCE

|                 |  |
|-----------------|--|
| Frequency Range | 5700 - 7125 MHz<br>Check our online SpecCheck for performance data of the particular combination of feed (TPA) and antenna |
| Polarization    | Dual Linear H + V  |
| VSWR            | Check our online SpecCheck for performance data of the particular combination of feed (TPA) and antenna                    |
| Impedance       | 50 Ohm   |

## COMPATIBLE WIRELESS PLATFORMS

|                   |  |
|-------------------|--|
| RF elements®      | any WB antenna: SH30WB, SH60WB, SH90WB, AH60WB, AH90WB, UD29WB<br>5 GHz Antennas: UH-TP-5-24, HG3-TP-S30, UD-TP-21, UD-TP-24, UD-TP-27 |
| Cambium Networks™ | ePMP 4600L, ePMP 4600C   |

## PRODUCT DIMENSIONS

