

Product Datasheet

Product ID: TP-ADAP-R5AC-PRISM



TwistPort™ Adaptor for Rocket 5AC Prism

ADAPTOR FOR ROCKET® 5AC PRISM

The TwistPort™ Adaptor for Rocket® 5AC Prism makes the Rocket® compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick locking waveguide port. Connecting and disconnecting the Rocket® 5AC Prism from the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA and 2x RP-SMA for GPS
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.36 Kg / 0.8 lbs – single unit 0.46 Kg / 1 lbs – single unit incl. package 10 Kg / 22 lbs – carton (20 units)
Single Unit	Retail Box: 17 × 13 × 10 cm
20 Units	Carton Box: 51.5 × 26.5 × 36.5 cm

PERFORMANCE

Frequency Range	5180 - 6400 MHz
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any TwistPort™ Antenna
Ubiquiti Networks®	Rocket® 5AC Prism, Rocket® 5AC Prism Gen2

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

